



## Flo-Guard breathing filter



Airway Management ▪ Breathing Filters

## Flo-Guard

### Low-resistance breathing filter for CPAP and bilevel

The Flo-Guard breathing filter is designed to be used at the machine end of a breathing system to protect the patient and machine against cross contamination, whilst maintaining a low resistance across a wide range of flow rates.

The low resistance makes it an ideal filter for use in both the hospital and the home where high flow rates may potentially be used, this includes CPAP, bilevel and cough assist applications.

The Flo-Guard offers an excellent bacterial and viral filtration efficiency whilst offering the lowest resistance to flow available at very high flow rates.

#### Electrostatic filter media

Providing an excellent filtration efficiency

#### Large surface area

To reduce resistance to flow

#### Clear housing

For good visibility

#### Conical shape

To aid airflow



Code	1690000
Box Qty.	50
Filtration efficiency	>99.99%
Resistance at 30L/min	0.4 cm H <sub>2</sub> O
Resistance at 60L/min	0.8cm H <sub>2</sub> O
Resistance at 90L/min	1.4cm H <sub>2</sub> O
Resistance at 120L/min	2.0cm H <sub>2</sub> O
Resistance at 150Lmin	2.7cm H <sub>2</sub> O
Resistance at 180L/min	3.4cm H <sub>2</sub> O
Resistance at 210L/min	4.3cm H <sub>2</sub> O
Resistance at 240L/min	5.1cm H <sub>2</sub> O
Compressible volume	80ml
Weight	27.8g
Connectors	22F-22M



Make an enquiry

IS12.19 • Issue 6 06.23



Intersurgical Ltd, Crane House, Molly Millars Lane, Wokingham, Berkshire, RG41 2RZ, UK  
 T: +44 (0)118 965 6300 info@intersurgical.com www.intersurgical.com



The manufacturer Intersurgical Ltd is certified to ISO 9001:2015, ISO 13485:2016, ISO 14001:2015 and MDSAP

**Please think before you print**  
 Save energy and paper.  
 If you must print this information sheet please print it double sided.